

# NACO-L 3077

## Slip and Leveling additive (Solvent Based)

Slip and Leveling additive for solvent-borne coating systems, improves leveling, prevents cratering, helps substrate wetting, acts as a defoamer and de-aeration aid, and does not interfere with inter-coat adhesion. Furthermore, prevents floating/flooding of organic pigments in combination with TiO<sub>2</sub>. The additive is recommended for baking enamels based on alkyd, acrylic or polyester resins, polyurethane coatings, two-pack epoxy coatings, and air-drying alkyd systems.

## Product Data

**Composition:** Modified acrylic copolymer

### Typical Properties:

**Note:** This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product.

**Physical Form:** Clear light yellowish liquid  
**Active Content:** 30%

## Applications

**Applications > Recommended for > Particularly Recommended:** Coatings > Solvent-based systems  
> All kinds of resin systems

### Recommended Levels:

**Note:** The properties and performance of the additive are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance before use.

**Based on**  
**Total formulation weight:** 0.5%

**Special Feature:** Compatible with all resin types

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.