

# NACO-DF 2040

## Defoamer and Air Release Additive (Polymer Based)

Silicone-free foam control agent for use in industrial and driveline lubricant applications. Particularly recommended for gear oils, special lubricants, hydraulic turbines, and transmission oils.

### Product Data

#### Composition:

Acrylate based foam inhibitor

#### Typical Properties:

**Note:** This information is intended as a guideline only and should not be used to issue specifications. Slight deviations do not affect application and capability of the product.

<b>Physical Form:</b>	Clear light yellow liquid
<b>Active Content:</b>	50%
<b>Flash point:</b>	38°C
<b>Density:</b>	0.85 g/ml
<b>Viscosity( 25° C):</b>	13 ± 3 s

### Applications

#### Applications > Recommended for > Particularly Recommended:

Oil industries > Industrial oils  
> Industrial and driveline lubricant

#### Recommended Levels:

**Note:** The properties and performance of the additive are greatly dependent upon the specific formulation in which it is utilized and, consequently, should always be tested (possibly at different treatment levels, temperatures, and/or time intervals) to verify performance before use.

<b>Based on</b>	
<b>Total formulation weight:</b>	0.02%

#### Special Feature:

Very low dosage

Our technical suggestions are based on data from many experiments and cannot represent a warranty of any kind as to their performance in other formulations. Customers must always verify our product's performance in their own systems. This technical data sheet replaces all previous issues.